

DOORSYSTEM



Sliding doors



The standard material used for DoorSystem's sliding door frames is stainless steel. We customize the frame and the opposite frame to your specifications and needs to give optimum flexibility in the door area.

Accessories include rail fencing, hall door fitted into door, double glazing, various types of locks and automatic solutions.

Sliding doors

With a sliding door from DoorSystem, you will have an INVISIBLE DOOR. Our sliding doors are manufactured either manually or automatically and are always customized to the individual conditions and specifications of your workplace.

Construction and design are simple to ensure better reliability and less maintenance. There is minimum demand for free space on the sides, giving optimum utilisation of the production facilities.

Door leaf and door frame come with a chamfer ideal for meeting the highest hygienic requirements.



DoorSystem use a silicone rubber for sealing as this type of sealing resists temperatures from -65°C to $+210^{\circ}\text{C}$, UV radiation, oxygen as well as several types of chemicals and solvents.



The DoorSystem handle is manufactured in stainless steel using a simple design but a strong structure. The position and design of the handle minimize the requirement for extra space.



Bottom guide and fittings are manufactured in stainless steel. The front guide roller is manufactured in strong nylon and is cone-shaped to obtain optimum door sealing.



DOORSYSTEM

Hovvejen 148
DK-8361 Hasselager
Denmark
Tel +45 86 92 11 71
Fax +45 86 92 11 81
www.doorsystem.dk
doorsystem@mail.dk